



CLEANING ■ SEALING ■ MAINTENANCE

Sealing and maintenance solutions for all types of stone, porcelain, quarry, terracotta and glazed ceramic

MATTSTONE TECHNICAL DATA SHEET REF: 12/5/1/.5

LTP MATTSTONE

Natural Finish Impregnating Sealer For interior & exterior use

Suitable for all types of natural and artificial stone, unglazed porcelain, sandstone, slate, marble, terracotta, quarry, brick & paving.

A natural, matt finish impregnating sealer that will delicately enhance colour and texture. Helps protect against staining. Strongly repels water, oil and grease. Allows surfaces to breathe.

Directions for use

Shake the bottle prior to use. Ensure surface to be treated is completely clean, dry and free from dirt, grime, cement and grout. Apply this sealer with a soft cloth or brush allowing at least two hours between coats. More absorbent floors may require further coats and on such floors the product should be generously applied. One hour after application, rub over the surface with a soft fluff free cloth or buffing machine to obtain a uniform finish and remove any material not yet absorbed. This product will dry after about two hours, but will take a further three days to become fully resistant. **N.B.** The aim is to completely fill the substrate with sealer without over applying it. Do not apply in direct sunlight. The sealer will help to inhibit oil based stains but such spillages should be wiped up immediately. On rougher surfaced floors it may be prudent to use an appropriate surface sealer in conjunction with this sealer. Use only in well ventilated areas.

Coverage

Per 10m²

Lower porosity floors - approximately 1-2 litres
Higher porosity floors - approximately 3-4 litres

Maintenance

Routinely sweep the floor and wash with LTP Waxwash. Clean walls and work surfaces with LTP Stonewash Spray. Every 3 – 4 years surfaces may require more intensive cleaning in which case use LTP Grimex. Surfaces may require a top up coat of sealer after intensive cleaning. Refer to LTP Grimex technical data sheet for more information.

This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area.

for beautiful surfaces we have the solutions...

LTP, Tone Estate, Milverton Road, Wellington, Somerset, TA21 0AN
T +44 (0) 1823 666213 F +44 (0) 1823 665685 E info@ltp-online.co.uk

www.ltp-online.co.uk

January 2013

Storage information

Store in a cool, dry, frost-free environment.

Shelf Life – Up to 4 years for un-opened containers.

Health & Safety

Contains: White Spirit (naphtha petroleum, hydrodesulphurised heavy (<0.1% benzene)). Flammable liquid and vapour. May be fatal if swallowed and enters airways. Toxic to aquatic life with long lasting effects.

Keep out of the reach of children. Store locked up. Avoid release to the environment. Wear protective gloves. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting, get medical advice/attention. Dispose of contents/container to hazardous waste collection point. Keep away from heat/sparks/open flames/hot surfaces.



Danger

VOC STATEMENT

EU Limit value for this product (Cat A/h) 750g/L (2010)
This product contains max 739g/L VOC

UN 1300

EC Label.EC No 1272/2008

